# 4x16 10/100/1000 SPAN Matrix Switch (4X16SP-1000BT)





The 4x16 Copper Gigabit SPAN Matrix Switch increases network visibility and leverages your investment in network analyzers, probes, and security equipment by allowing you to simultaneously monitor up to four separate SPAN ports. Greater visibility accelerates problem resolution, reduces downtime, increases enterprise productivity, and improves ROI.

Like all Datacom Systems matrix switches, the 4X16SP-1000BT matrix switch is compatible with all vendor hardware and can be controlled by our free MANA*gents*™ switch control software, which will allow you to control all of your matrix switches through a single interface regardless of what network appliances you choose to deploy.

- Leverages up to four network appliances across 16 SPAN/ mirror ports in Gigabit Ethernet environments
- Daisy-chain up to four units to access up to 64 SPAN/mirror ports in Gigabit Ethernet networks
- Manage your matrix switch from the same console or browser used by the network appliance
- Central management of matrix switches eliminates the need to travel with portable equipment
- Ideal for networks using distributed network analyzers save money by deploying and maintaining fewer devices on your network
- Optimal for network access and distribution layer visibility
- Remote deployment speeds problem resolution time
- Allows four protocol analyzers or other network devices to analyze/monitor the same SPAN port
- Easily configured or switched through our free MANAgents<sup>™</sup> switch control software or directly through the API of most network analyzers
- Conveniently rack-mountable in only 1U (1.72")

## TECHNICAL SPECIFICATIONS

#### Ports

Sixteen (16) - 10/100/1000 (RJ45) Network Connections Four (4) - 10/100/1000 (RJ45) Common Connections Two (2) - USB Control Connections RJ45 Daisy Connection

### **Power Requirements**

120VAC, 80W

#### Input/Output

100-240V 50-60Hz 25W

#### Physical Dimensions (H x W x D)

1.72 x 19 x 11 in. 4.37 x 48.26 x 27.94 cm.

### Weight

12 lbs. 5.45 Kgs.

### **Environmental**

Operating Temperature: 0° to 40° C Storage Temperature: 30° to 65° C Humidity: Less than 95° C non-condensing

### Certifications

EN 50082-1 61000-4 Series EN 55022 Class B Low Voltage Directive 72-23-EEC (1993) CFR 47 Part 15 Class B CE

### **Warranty**

2-year limited warranty

### **Ordering Information**

Product Description 4X16SP-1000BT 4x16 10/100/1000 SPAN Matrix Switch